

ES-NRAMB-44365 XM

4 MP AI Smart Infrared Light Fixed-Lens Built-in-Mic Bullet Network Camera



Functions

Artificial Intelligence

In the field of physical security, Ecovision Artificial Intelligence analytics uses powerful algorithms to automate detection, categorization, and analysis of objects and motions in a camera's view. It reduces costs, speeds up responses, and facilitates new practices and processes.

Smart Infrared Light

Smart IR allows the camera to reduce or increase the level of infrared light it projects based upon the subject's distance. cameras that adjusts the intensity of the camera's infrared LEDs to compensate for the distance of an object so that the infrared does not overexpose the object. This allows the image to not get "washed out" by over-exposing the subject.

Humanoid Detection

Advanced algorithms are used to differentiate and send an alarm when human and vehicular shapes are detected. False alerts are filtered for up to 95% accuracy, saving customers the hassle of unwanted alarms. Video clips recorded with Motion Detection enabled cameras get sorted into "Files". Making it easy to play back, review and retrieve historical information. Motion Detection alerts can be viewed on the Mobile app for iOS and Android.

Perimeter Protection

Perimeter security is a term that represents a broad range of physical security options such as access control, gates, barriers and other security controls, a camera with video analytics protect the perimeter in a reliable and cost-effective manner.

- **4.0MP 1/3" SC401AI** Low illumination and high definition image CMOS sensor.
- **Smart IR** allows the image to not get "washed out" by over-exposing the subject.
- **Best "True Day/Night"** with Smart IRC Physical Filter.
- **Advanced H.265AI** (Compatible with H.265/H.264) video compression, super low rate, high definition quality image.
- **Support ONVIF**, access third party, Support various mobile monitoring, Support cloud technology.
- **Built-in IR LED**, the max. Infrared Radiation distance is 30 Mtr.
- **Image Features:** Support 2D/3D NR, Digital Wide Dynamic Range (WDR) / Automatic Gain Control (AGC).
- **Sound Management:** 30 ft of audio pickup range with its built-in MIC and noise reduction algorithms.
- **12 VDC/PoE** power supply, easy for installation.

Smart H.265+

With H.265+, video quality nearly matches that of H.265/HEVC but reduces the transmission bandwidth and storage capacity required, due to three key technologies — prediction encoding, noise suppression, and flexible bitrate control. It demonstrates incredible improvements in bandwidth reduction, data storage efficiency, and video content analyses.

Wide Dynamic Range (WDR)

With high-performance sensor and large aperture lens, Ecovision WDR technology improves a camera's image quality under high-contrast lighting conditions where both dimly and brightly lit areas are present in the field of view. It enables the camera to capture details clearly in both the poorly and strongly illuminated areas of the video.

Built-in mic

With High-Fidelity microphone, Ecovision built-in mic can effectively filtered noise and save live sound. simply connect the camera to your recorder and make sure the audio stream is enabled. Do not require any additional cable or accessories and send audio mixed directly with the video stream.

Protection (IP67, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak.

Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification

Camera

Image Sensor	1/3" CMOS
Max. Resolution	2688 (H) × 1520 (V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/50 s–1/100,000 s
Min. Illumination	0.02 Lux/F2.0, 30IRE, 0 Lux IR on
S/N Ratio	>56 dB
Illumination Distance	up to 30 m (98.43 ft) (IR)
Illuminator On/Off Control	Auto; Manual
Illuminator Number	4 (IR LED)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–180° Rotation: 0°–360°

Lens

Lens Type		Fixed-LENS			
Focal Length		3.6 mm			
Max. Aperture		F1.6			
Field of View		3.6 mm: H: 78°; V: 41°; D: 94°			
Iris Control		YES			
Close Focus Distance		3.6 mm: 1.6 m (5.25 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	3.6 mm	85.4 m (280.18 ft)	34.2 m (112.20 ft)	17.1 m (56.10 ft)	8.5 m (27.89 ft)

Intelligence

Intelligence analysis	Supporting human detection, face detection, and support to customize other intelligent functions
Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos

Video

Video Compression	H.264H; H.265; H.264; H.264B; MJPEG (Only supported by the sub stream)
Smart Codec	Smart H.265+
Video Frame Rate	Main stream: 2688 × 1520@(1–20 fps)/2560 × 1440@(1–25/30 fps) Sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Stream Capability	2 streams
Resolution	4M (2688 × 1520); 3.6M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.265: 12 kbps–6144 kbps
Day/Night	Auto (ICR) / Manual
BLC	Yes
WDR	120 dB
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Gain Control	Auto; Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (rectangular)
Region of Interest (RoI)	Yes (4 areas)
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 2688 × 1520 resolution and lower)
Mirror	Yes
Privacy Masking	YES
Anti Flicker	Yes

Audio

Built-in MIC	Yes
Audio Compression	G.711a; G.711Mu; PCM; G.726

Network

Network Port	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Interoperability	ONVIF (Profile S/Profile T); CGI; P2P; Milestone
User/Host	6 (Total bandwidth: 36 M)
Storage	FTP; SFTP;
Browser	IE; Chrome; Firefox
Management Software	xmeye
Mobile Client	iOS; Android